



Double Base Powders

SAFETY DATA SHEET

June 2017

The following smokeless powders are
distributed by Hodgdon Powder Company.

Hi-Skor 700X TM **(EX-2016090001)**

Hi-Skor 800X TM **(EX-2016090001)**

Clays (AS-30N) **(EX-2013031259)**

International (AS-50N) **(EX-2015110878)**

Universal (AP-70N) **(EX-2012010792)**

1.4C EX Approval Number in Bold Parenthesis

Propellant AS30N

Thales (Thales Australia Limited)

Chemwatch: 47139
Version No: 10.1.1.1
Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 4

Issue Date: 21/05/2013
Print Date: 05/03/2015
Initial Date: Not Available
S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Propellant AS30N
Synonyms	Propellant AS30N V02
Proper shipping name	POWDER, SMOKELESS†
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Porous double-base smokeless powders or propellant for shotgun ammunition.
--------------------------	--

Details of the manufacturer/importer

Registered company name	Thales (Thales Australia Limited)	Thales (Thales Australia Limited)
Address	Private Bag 1 Mulwala 2647 NSW Australia	Bayly Street Mulwala 2647 NSW Australia
Telephone	Not Available	+61 3 5742 2200
Fax	Not Available	+61 3 5744 1873
Website	Not Available	Not Available
Email	Not Available	Not Available

Emergency telephone number

Association / Organisation	Not Available	Thales Australia Mulwala Facility
Emergency telephone numbers	Not Available	03 5742 2200
Other emergency telephone numbers	Not Available	Not Available

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture




HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the Model WHS Regulations and the ADG Code.

CHEMWATCH HAZARD RATINGS

	Min	Max	
Flammability	3	4	0 = Minimum 1 = Low 2 = Moderate 3 = High 4 = Extreme
Toxicity	4	4	
Body Contact	4	4	
Reactivity	4	4	
Chronic	2	2	

Poisons Schedule	Not Applicable
GHS Classification [1]	Explosive Division 1.3, Acute Toxicity (Oral) Category 2, Acute Toxicity (Dermal) Category 1, Acute Toxicity (Inhalation) Category 2, STOT - RE Category 2, Chronic Aquatic Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

Label elements

GHS label elements	  
--------------------	---

SIGNAL WORD	DANGER
-------------	---------------

Hazard statement(s)

H203	Explosive; fire, blast or projection hazard
H300	Fatal if swallowed
H310	Fatal in contact with skin

Continued...

Propellant AS30N

H330	Fatal if inhaled
H373	May cause damage to organs through prolonged or repeated exposure
H412	Harmful to aquatic life with long lasting effects

Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P230	Keep wetted with phlegmatizer
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P262	Do not get in eyes, on skin, or on clothing.

Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P330	Rinse mouth.
P361+P364	Take off immediately all contaminated clothing and wash it before reuse.

Precautionary statement(s) Storage

P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P401	Store according to local regulations for explosives

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration
------	--

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
9004-70-0	>85	nitrocellulose
55-63-0	10	nitroglycerin
Not Available	<10	additives nonhazardous

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Wash out immediately with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor.
Ingestion	<ul style="list-style-type: none"> ▶ For advice, contact a Poisons Information Centre or a doctor at once. ▶ Urgent hospital treatment is likely to be needed. ▶ If swallowed do NOT induce vomiting. ▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▶ Observe the patient carefully. ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▶ Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

Symptoms of vasodilation and reflex tachycardia may present following organic nitrate overdose; most organic nitrates are extensively metabolised by hydrolysis to inorganic nitrites. Organic nitrates and nitrites are readily absorbed through the skin, lungs, mucosa and gastro-intestinal tract.

SECTION 5 FIREFIGHTING MEASURES

Propellant AS30N

Extinguishing media

	<p>DANGER: Deliver media remotely.</p> <ul style="list-style-type: none"> ▶ For minor fires: Flooding quantities only. ▶ For large fires: Do not attempt to extinguish.
--	---

Special hazards arising from the substrate or mixture

Fire Incompatibility	<ul style="list-style-type: none"> ▶ Avoid contact with other explosives, pyrotechnics, solvents, adhesives, paints, cleaners and unauthorized metals, plastics, packing equipment and materials. ▶ Avoid contamination with acids, alkalis, reducing agents, amines and phosphorus.
-----------------------------	--

Advice for firefighters

Fire Fighting	<p>WARNING: EXPLOSIVE MATERIALS / ARTICLES PRESENT!</p> <ul style="list-style-type: none"> ▶ Evacuate all personnel and move upwind. ▶ Prevent re-entry. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ May be explosively reactive, detonate and release much heat.
Fire/Explosion Hazard	<p>WARNING: HIGH EXPLOSION HAZARD!</p> <ul style="list-style-type: none"> ▶ Combustible. ▶ Will burn with rapidly increasing intensity of fire. ▶ Dry material is extremely sensitive to shock, friction, heat and sparks. ▶ Avoid metal to metal contact.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills	<p>Clean up all spills immediately. Avoid contact with skin and eyes. Wear impervious gloves and safety glasses. Use spark-free tools when handling Remove all ignition sources.</p>
Major Spills	<p>Clear area of personnel. Restrict access to area. Alert Fire Brigade and tell them location and nature of hazard.</p> <ul style="list-style-type: none"> ▶ May be violently or explosively reactive.
<p>Personal Protective Equipment advice is contained in Section 8 of the MSDS.</p>	

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	<p>Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this MSDS. Avoid all personal contact, including inhalation Wear protective clothing when risk of exposure occurs.</p> <ul style="list-style-type: none"> ▶ Avoid smoking, naked lights, heat or ignition sources <p>Must not be struck by metal implements.</p>
Other information	<p>Store in original containers.</p> <ul style="list-style-type: none"> ▶ No smoking, naked lights, heat or ignition sources. <p>Keep dry.</p> <ul style="list-style-type: none"> ▶ Keep storage area free of debris, waste and combustibles.

Conditions for safe storage, including any incompatibilities

Suitable container	<p>Explosives Code Packing Instruction P114(b) or 114(b) General packaging provisions of 4.1.1, 4.1.3 and special provision 4.1.5 are to be met. For UN 0160, 0161 - If outer packaging is drum then inner packaging is not required. For UN 0160, 0161 - If outer packaging is 1A2 or 1B2 metal drums then drum construction shall be that risk of explosion, by reason of increase by internal pressure from internal or external causes, is prevented. For UN 0077, 0132, 0234, 0235, 0236, packagings are to be lead free, otherwise: Inner Packagings: Bags: Paper Kraft, Plastics, Textiles - sift proof, Woven Plastic - sift proof Receptacles: Fibreboard, Metal, Paper, Plastic, Woven Plastic - sift proof Intermediate Packagings: Not necessary Outer Packagings: Boxes: Natural Wood (4C1), Natural Wood -sift proof (4C2), Plywood (4D), Reconstituted Wood (4F), Fibreboard (4G) Drums: Steel, Removable Head (1A2), Aluminium, removable head (1B2), Plywood (1D), Fibre (1G), Plastic, removable head (1H2) Check containers are clearly labelled.</p>
Storage incompatibility	<p>Segregate from strong acids strong alkalis and strong oxidisers</p> <ul style="list-style-type: none"> ▶ Avoid contact with other explosives, pyrotechnics, solvents, adhesives, paints, cleaners and unauthorized metals, plastics, packing equipment and materials. ▶ Avoid contamination with acids, alkalis, reducing agents, amines and phosphorus.

Propellant AS30N



- X — Must not be stored together
- 0 — May be stored together with specific preventions
- + — May be stored together

PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	nitrocellulose	Fume (thermally generated) (respirable dust)(g)	2 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	nitroglycerin	Nitroglycerin (NG)	0.46 mg/m3 / 0.05 ppm	Not Available	Not Available	Sk

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
nitrocellulose	Pyroxylin; (Cellulose tetranitrate)	15 mg/m3	170 mg/m3	990 mg/m3
nitroglycerin	Nitroglycerin	0.1 mg/m3	2 mg/m3	500 mg/m3

Ingredient	Original IDLH	Revised IDLH
nitrocellulose	Not Available	Not Available
nitroglycerin	500 mg/m3	75 mg/m3
additives nonhazardous	Not Available	Not Available

Exposure controls

Appropriate engineering controls	<p>Use in a well-ventilated area</p> <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.</p>
Personal protection	
Eye and face protection	<ul style="list-style-type: none"> ▶ Safety glasses with side shields. ▶ Chemical goggles. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Skin protection	See Hand protection below
Hands/feet protection	<p>Wear protective gloves, e.g. PVC.</p> <ul style="list-style-type: none"> ▶ Protective footwear
Body protection	See Other protection below
Other protection	<p>Overalls</p> <ul style="list-style-type: none"> ▶ Eyewash unit. ▶ Impervious apron <p>Ensure there is ready access to a safety shower</p> <ul style="list-style-type: none"> ▶ Barrier cream
Thermal hazards	Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the: "Forsberg Clothing Performance Index". The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:
Propellant AS30N Not Available

Material	CPI

* CPI - Chemwatch Performance Index
A: Best Selection

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator

Propellant AS30N

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Small grey, green-grey or orange-grey disc shaped granules.		
Physical state	Divided Solid	Relative density (Water = 1)	Approx. 0.6
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	170
pH (as supplied)	Not Applicable	Decomposition temperature	Explosive.
Melting point / freezing point (°C)	170	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Negligible
Vapour pressure (kPa)	Negligible	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution	Not Applicable
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▶ Product is considered stable under normal handling conditions. ▶ Stable under normal storage conditions. ▶ Hazardous polymerization will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Very toxic by inhalation. The decomposition vapours are harmful if inhaled in large volume.
Ingestion	Severely toxic effects may result from the accidental ingestion of the material; animal experiments indicate that ingestion of less than 5 gram may be fatal or may produce serious damage to the health of the individual. The substance and/or its metabolites may bind to haemoglobin inhibiting normal uptake of oxygen. This condition, known as "methaemoglobinemia", is a form of oxygen starvation (anoxia). Symptoms include cyanosis (a bluish discolouration skin and mucous membranes) and breathing difficulties.
Skin Contact	Skin contact with the material may produce severely toxic effects; systemic effects may result following absorption and these may be fatal. The material is not thought to be a skin irritant (as classified by EC Directives using animal models). Abrasive damage however, may result from prolonged exposures. Open cuts, abraded or irritated skin should not be exposed to this material Bare unprotected skin should not be exposed to this material The material may accentuate any pre-existing dermatitis condition
Eye	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may cause transient discomfort characterised by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result.

Propellant AS30N

Chronic	The principal hazard is related to the potential of fire/explosion and associated physical injury and toxic fume inhalation. Substance accumulation, in the human body, is likely and may cause some concern following repeated or long-term occupational exposure. There is limited evidence that, skin contact with this product is more likely to cause a sensitisation reaction in some persons compared to the general population.	
Propellant AS30N	TOXICITY	IRRITATION
	Not Available	Not Available
nitrocellulose	TOXICITY	IRRITATION
	Oral (rat) LD50: >5000 mg/kg ^[2]	Not Available
nitroglycerin	TOXICITY	IRRITATION
	dermal (rat) LD50: >9 mg/kg ^[1]	Not Available
	Oral (rat) LD50: 105 mg/kg ^[2]	
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's msds Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

NITROCELLULOSE	No significant acute toxicological data identified in literature search.
NITROGLYCERIN	The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Substance has been investigated as a tumorigen, mutagen and reproductive effector. Equivocal tumorigen by RTECS criteria. Reproductive effector in rats.

Acute Toxicity	✓	Carcinogenicity	⊖
Skin Irritation/Corrosion	⊖	Reproductivity	⊖
Serious Eye Damage/Irritation	⊖	STOT - Single Exposure	⊖
Respiratory or Skin sensitisation	⊖	STOT - Repeated Exposure	✓
Mutagenicity	⊖	Aspiration Hazard	⊖

Legend: ✓ – Data required to make classification available
 ✗ – Data available but does not fill the criteria for classification
 ⊖ – Data Not Available to make classification

CMR STATUS

SKIN	nitroglycerin	Australia Exposure Standards - Skin	Sk
-------------	---------------	-------------------------------------	----

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
nitroglycerin	LOW (Half-life = 14 days)	LOW (Half-life = 0.73 days)

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 DISPOSAL CONSIDERATIONS


Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> Explosives must not be thrown away, buried, discarded or placed with garbage. Explosives which are surplus, deteriorated or considered unsafe for transport, storage or use shall be destroyed and the statutory authorities shall be notified. This material may be disposed of by burning or detonation but the operation may only be performed under the control of a person trained in the safe destruction of explosives.
-------------------------------------	--

Propellant AS30N

SECTION 14 TRANSPORT INFORMATION

Labels Required

	
Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG)

UN number	0161
Packing group	Not Applicable
UN proper shipping name	POWDER, SMOKELESS†
Environmental hazard	No relevant data
Transport hazard class(es)	Class : 1.3C Subrisk : Not Applicable
Special precautions for user	Special provisions : Not Applicable Limited quantity : 0

Air transport (ICAO-IATA / DGR)

UN number	0161
Packing group	Not Applicable
UN proper shipping name	Powder, smokeless †
Environmental hazard	No relevant data
Transport hazard class(es)	ICAO/IATA Class : 1.3C ICAO / IATA Subrisk : Not Applicable ERG Code : 1L
Special precautions for user	Special provisions : Not Applicable Cargo Only Packing Instructions : Forbidden Cargo Only Maximum Qty / Pack : Forbidden Passenger and Cargo Packing Instructions : Forbidden Passenger and Cargo Maximum Qty / Pack : Forbidden Passenger and Cargo Limited Quantity Packing Instructions : Forbidden Passenger and Cargo Limited Maximum Qty / Pack : Forbidden

Sea transport (IMDG-Code / GGVSee)

UN number	0161
Packing group	Not Applicable
UN proper shipping name	POWDER, SMOKELESS
Environmental hazard	Not Applicable
Transport hazard class(es)	IMDG Class : 1.3C IMDG Subrisk : Not Applicable
Special precautions for user	EMS Number : F-B , S-Y Special provisions : Not Applicable Limited Quantities : 0

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

nitrocellulose(9004-70-0) is found on the following regulatory lists	"Australia Exposure Standards","Australia Inventory of Chemical Substances (AICS)","International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs","International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft","Australia Hazardous Substances Information System - Consolidated Lists"
nitroglycerin(55-63-0) is found on the following regulatory lists	"Australia Exposure Standards","Australia Inventory of Chemical Substances (AICS)","International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft","Australia Hazardous Substances Information System - Consolidated Lists"

Propellant AS30N

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Notes

When the propellant is packed as in packaging UN4GY12.5/S**AUS/ABBE 30818 it is suitable for air transport as follows

Air Transport IATA:

ICAO/IATA Class: 1.4C ICAO/IATA Subrisk: None

UN/ID Number: 0509 Packing Group: -

Special provisions: None

Cargo Only

Packing Instructions: 114 Maximum Qty/Pack: 5kg

Packing Instructions: Forbidden Maximum Qty/Pack: Forbidden

Passenger and Cargo Passenger and Cargo

Limited Quantity Limited Quantity

Packing Instructions: Forbidden Maximum Qty/Pack: Forbidden

This is the end of the MSDS.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Propellant AP70N

Thales (Thales Australia Limited)

Chemwatch Hazard Alert Code: 4

Chemwatch: 4693-60

Version No: 5.1.1.1

Safety Data Sheet according to WHS and ADG requirements

Issue Date: 21/05/2013

Print Date: 05/03/2015

Initial Date: Not Available

S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Propellant AP70N
Synonyms	Not Available
Proper shipping name	POWDER, SMOKELESS†
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Porous double-base smokeless powders or propellant for pistol ammunition.
--------------------------	---

Details of the manufacturer/importer

Registered company name	Thales (Thales Australia Limited)	Thales (Thales Australia Limited)
Address	Private Bag 1 Mulwala 2647 NSW Australia	Bayly Street Mulwala 2647 NSW Australia
Telephone	Not Available	+61 3 5742 2200
Fax	Not Available	+61 3 5744 1873
Website	Not Available	Not Available
Email	Not Available	Not Available

Emergency telephone number

Association / Organisation	Not Available	Thales Australia Mulwala Facility
Emergency telephone numbers	Not Available	03 5742 2200
Other emergency telephone numbers	Not Available	Not Available

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture




HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the Model WHS Regulations and the ADG Code.

CHEMWATCH HAZARD RATINGS

	Min	Max	
Flammability	3	4	0 = Minimum 1 = Low 2 = Moderate 3 = High 4 = Extreme
Toxicity	4	4	
Body Contact	4	4	
Reactivity	4	4	
Chronic	2	2	

Poisons Schedule	Not Applicable
GHS Classification [1]	Explosive Division 1.3, Acute Toxicity (Oral) Category 2, Acute Toxicity (Dermal) Category 1, Acute Toxicity (Inhalation) Category 2, STOT - RE Category 2, Chronic Aquatic Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

Label elements

GHS label elements	  
--------------------	---

SIGNAL WORD	DANGER
-------------	---------------

Hazard statement(s)

H203	Explosive; fire, blast or projection hazard
H300	Fatal if swallowed
H310	Fatal in contact with skin

Continued...

Propellant AP70N

H330	Fatal if inhaled
H373	May cause damage to organs through prolonged or repeated exposure
H412	Harmful to aquatic life with long lasting effects

Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P230	Keep wetted with phlegmatizer
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P262	Do not get in eyes, on skin, or on clothing.

Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P330	Rinse mouth.
P361+P364	Take off immediately all contaminated clothing and wash it before reuse.

Precautionary statement(s) Storage

P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P401	Store according to local regulations for explosives

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration
------	--

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
9004-70-0	>85	nitrocellulose
55-63-0	10	nitroglycerin
Not Available	<10	additives nonhazardous

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Immediately hold eyelids apart and flush the eye continuously with running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. ▶ Transport to hospital or doctor without delay. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor.
Ingestion	<ul style="list-style-type: none"> ▶ For advice, contact a Poisons Information Centre or a doctor at once. ▶ Urgent hospital treatment is likely to be needed. ▶ If swallowed do NOT induce vomiting. ▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▶ Observe the patient carefully. ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▶ Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

Symptoms of vasodilation and reflex tachycardia may present following organic nitrate overdose; most organic nitrates are extensively metabolised by hydrolysis to inorganic nitrites. Organic nitrates and nitrites are readily absorbed through the skin, lungs, mucosa and gastro-intestinal tract.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

	<p>DANGER: Deliver media remotely.</p> <ul style="list-style-type: none"> ▶ For minor fires: Flooding quantities only. ▶ For large fires: Do not attempt to extinguish.
--	---

Special hazards arising from the substrate or mixture

Fire Incompatibility	<ul style="list-style-type: none"> ▶ Avoid contact with other explosives, pyrotechnics, solvents, adhesives, paints, cleaners and unauthorized metals, plastics, packing equipment and materials. ▶ Avoid contamination with acids, alkalis, reducing agents, amines and phosphorus.
-----------------------------	--

Advice for firefighters

Fire Fighting	<p>WARNING: EXPLOSIVE MATERIALS / ARTICLES PRESENT!</p> <ul style="list-style-type: none"> ▶ Evacuate all personnel and move upwind. ▶ Prevent re-entry. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ May be explosively reactive, detonate and release much heat.
Fire/Explosion Hazard	<p>WARNING: HIGH EXPLOSION HAZARD!</p> <ul style="list-style-type: none"> ▶ Combustible. ▶ Will burn with rapidly increasing intensity of fire. ▶ Dry material is extremely sensitive to shock, friction, heat and sparks. ▶ Avoid metal to metal contact.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills	<p>Clean up all spills immediately. Avoid contact with skin and eyes. Wear impervious gloves and safety glasses. Use spark-free tools when handling Remove all ignition sources.</p>
Major Spills	<p>Clear area of personnel. Restrict access to area. Alert Fire Brigade and tell them location and nature of hazard.</p> <ul style="list-style-type: none"> ▶ May be violently or explosively reactive.
	<p>Personal Protective Equipment advice is contained in Section 8 of the MSDS.</p>

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	<p>Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this MSDS. Avoid all personal contact, including inhalation Wear protective clothing when risk of exposure occurs.</p> <ul style="list-style-type: none"> ▶ Avoid smoking, naked lights, heat or ignition sources <p>Must not be struck by metal implements.</p>
Other information	<p>Store in original containers.</p> <ul style="list-style-type: none"> ▶ No smoking, naked lights, heat or ignition sources. <p>Keep dry.</p> <ul style="list-style-type: none"> ▶ Keep storage area free of debris, waste and combustibles.

Conditions for safe storage, including any incompatibilities

Suitable container	<p>Explosives Code Packing Instruction P114(b) or 114(b) General packaging provisions of 4.1.1, 4.1.3 and special provision 4.1.5 are to be met. For UN 0160, 0161 - If outer packaging is drum then inner packaging is not required. For UN 0160, 0161 - If outer packaging is 1A2 or 1B2 metal drums then drum construction shall be that risk of explosion, by reason of increase by internal pressure from internal or external causes, is prevented. For UN 0077, 0132, 0234, 0235, 0236, packagings are to be lead free, otherwise: Inner Packagings: Bags: Paper Kraft, Plastics, Textiles - sift proof, Woven Plastic - sift proof Receptacles: Fibreboard, Metal, Paper, Plastic, Woven Plastic - sift proof Intermediate Packagings: Not necessary Outer Packagings: Boxes: Natural Wood (4C1), Natural Wood -sift proof (4C2), Plywood (4D), Reconstituted Wood (4F), Fibreboard (4G) Drums: Steel, Removable Head (1A2), Aluminium, removable head (1B2), Plywood (1D), Fibre (1G), Plastic, removable head (1H2) Check containers are clearly labelled.</p>
Storage incompatibility	<p>Segregate from strong acids strong alkalis and strong oxidisers</p> <ul style="list-style-type: none"> ▶ Avoid contact with other explosives, pyrotechnics, solvents, adhesives, paints, cleaners and unauthorized metals, plastics, packing equipment and materials. ▶ Avoid contamination with acids, alkalis, reducing agents, amines and phosphorus.

Propellant AP70N



- X** — Must not be stored together
0 — May be stored together with specific preventions
+ — May be stored together

PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	nitrocellulose	Fume (thermally generated) (respirable dust)(g)	2 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	nitroglycerin	Nitroglycerin (NG)	0.46 mg/m3 / 0.05 ppm	Not Available	Not Available	Sk

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
nitrocellulose	Pyroxylin; (Cellulose tetranitrate)	15 mg/m3	170 mg/m3	990 mg/m3
nitroglycerin	Nitroglycerin	0.1 mg/m3	2 mg/m3	500 mg/m3

Ingredient	Original IDLH	Revised IDLH
nitrocellulose	Not Available	Not Available
nitroglycerin	500 mg/m3	75 mg/m3
additives nonhazardous	Not Available	Not Available

Exposure controls

Appropriate engineering controls	<p>Use in a well-ventilated area</p> <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.</p>
Personal protection	
Eye and face protection	<ul style="list-style-type: none"> ▶ Safety glasses with side shields. ▶ Chemical goggles. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Skin protection	See Hand protection below
Hands/feet protection	<p>Wear protective gloves, e.g. PVC.</p> <ul style="list-style-type: none"> ▶ Protective footwear
Body protection	See Other protection below
Other protection	<p>Overalls</p> <ul style="list-style-type: none"> ▶ Eyewash unit. ▶ Impervious apron <p>Ensure there is ready access to a safety shower</p> <ul style="list-style-type: none"> ▶ Barrier cream
Thermal hazards	Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

Propellant AP70N Not Available

Material	CPI

* CPI - Chemwatch Performance Index

A: Best Selection

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator

Continued...

Propellant AP70N

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Small grey, green-grey or orange-grey disc shaped granules.		
Physical state	Divided Solid	Relative density (Water = 1)	Approx. 0.6
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	170
pH (as supplied)	Not Applicable	Decomposition temperature	Explosive.
Melting point / freezing point (°C)	170	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Negligible
Vapour pressure (kPa)	Negligible	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution	Not Applicable
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▶ Product is considered stable under normal handling conditions. ▶ Stable under normal storage conditions. ▶ Hazardous polymerization will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Very toxic by inhalation. The decomposition vapours are harmful if inhaled in large volume.
Ingestion	Severely toxic effects may result from the accidental ingestion of the material; animal experiments indicate that ingestion of less than 5 gram may be fatal or may produce serious damage to the health of the individual. The substance and/or its metabolites may bind to haemoglobin inhibiting normal uptake of oxygen. This condition, known as "methaemoglobinemia", is a form of oxygen starvation (anoxia). Symptoms include cyanosis (a bluish discolouration skin and mucous membranes) and breathing difficulties.
Skin Contact	Skin contact with the material may produce severely toxic effects; systemic effects may result following absorption and these may be fatal. The material is not thought to be a skin irritant (as classified by EC Directives using animal models). Abrasive damage however, may result from prolonged exposures. Open cuts, abraded or irritated skin should not be exposed to this material Bare unprotected skin should not be exposed to this material The material may accentuate any pre-existing dermatitis condition
Eye	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may cause transient discomfort characterised by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result.

Propellant AP70N

Chronic	The principal hazard is related to the potential of fire/explosion and associated physical injury and toxic fume inhalation. Substance accumulation, in the human body, is likely and may cause some concern following repeated or long-term occupational exposure. There is limited evidence that, skin contact with this product is more likely to cause a sensitisation reaction in some persons compared to the general population.	
Propellant AP70N	TOXICITY Not Available	IRRITATION Not Available
nitrocellulose	TOXICITY Oral (rat) LD50: >5000 mg/kg ^[2]	IRRITATION Not Available
nitroglycerin	TOXICITY dermal (rat) LD50: >9 mg/kg ^[1] Oral (rat) LD50: 105 mg/kg ^[2]	IRRITATION Not Available
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's msds Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

NITROCELLULOSE	No significant acute toxicological data identified in literature search.
NITROGLYCERIN	The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Substance has been investigated as a tumorigen, mutagen and reproductive effector. Equivocal tumorigen by RTECS criteria. Reproductive effector in rats.

Acute Toxicity	✔	Carcinogenicity	⊘
Skin Irritation/Corrosion	⊘	Reproductivity	⊘
Serious Eye Damage/Irritation	⊘	STOT - Single Exposure	⊘
Respiratory or Skin sensitisation	⊘	STOT - Repeated Exposure	✔
Mutagenicity	⊘	Aspiration Hazard	⊘

Legend: ✔ – Data required to make classification available
 ✘ – Data available but does not fill the criteria for classification
 ⊘ – Data Not Available to make classification

CMR STATUS

SKIN	nitroglycerin	Australia Exposure Standards - Skin	Sk
-------------	---------------	-------------------------------------	----

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
nitroglycerin	LOW (Half-life = 14 days)	LOW (Half-life = 0.73 days)

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> ▶ Explosives must not be thrown away, buried, discarded or placed with garbage. ▶ Explosives which are surplus, deteriorated or considered unsafe for transport, storage or use shall be destroyed and the statutory authorities shall be notified. ▶ This material may be disposed of by burning or detonation but the operation may only be performed under the control of a person trained in the safe destruction of explosives.
-------------------------------------	--

SECTION 14 TRANSPORT INFORMATION

Labels Required

	
Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG)

UN number	0161
Packing group	Not Applicable
UN proper shipping name	POWDER, SMOKELESS†
Environmental hazard	No relevant data
Transport hazard class(es)	Class : 1.3C Subrisk : Not Applicable
Special precautions for user	Special provisions : Not Applicable Limited quantity : 0

Air transport (ICAO-IATA / DGR)

UN number	0161
Packing group	Not Applicable
UN proper shipping name	Powder, smokeless †
Environmental hazard	No relevant data
Transport hazard class(es)	ICAO/IATA Class : 1.3C ICAO / IATA Subrisk : Not Applicable ERG Code : 1L
Special precautions for user	Special provisions : Not Applicable Cargo Only Packing Instructions : Forbidden Cargo Only Maximum Qty / Pack : Forbidden Passenger and Cargo Packing Instructions : Forbidden Passenger and Cargo Maximum Qty / Pack : Forbidden Passenger and Cargo Limited Quantity Packing Instructions : Forbidden Passenger and Cargo Limited Maximum Qty / Pack : Forbidden

Sea transport (IMDG-Code / GGVSee)

UN number	0161
Packing group	Not Applicable
UN proper shipping name	POWDER, SMOKELESS
Environmental hazard	Not Applicable
Transport hazard class(es)	IMDG Class : 1.3C IMDG Subrisk : Not Applicable
Special precautions for user	EMS Number : F-B , S-Y Special provisions : Not Applicable Limited Quantities : 0

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

nitrocellulose(9004-70-0) is found on the following regulatory lists	"Australia Exposure Standards","Australia Inventory of Chemical Substances (AICS)","International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs","International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft","Australia Hazardous Substances Information System - Consolidated Lists"
nitroglycerin(55-63-0) is found on the following regulatory lists	"Australia Exposure Standards","Australia Inventory of Chemical Substances (AICS)","International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft","Australia Hazardous Substances Information System - Consolidated Lists"

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Notes

When the propellant is packed as in packaging UN4GY12.5/S/**/AUS/ABBE 30818 it is suitable for air transport as follows:

Air Transport IATA:

ICAO/IATA Class 1.4C ICAO/IATA Subrisk: None

UN/ID Number 0509 Packing Group:-

Special Provisions: None

Cargo only

Packing Instructions: 114 Maximum Qty/Pack: 5kg

Passenger and Cargo

Packing Instructions: Forbidden Maximum Qty/Pack: Forbidden

Passenger and Cargo

Limited Quantity

Packing Instructions: Forbidden Maximum Qty/Pack: Forbidden

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Propellant AS50N

Thales (Thales Australia Limited)

Chemwatch Hazard Alert Code: 4

Chemwatch: 4693-59

Version No: 4.1.1.1

Safety Data Sheet according to WHS and ADG requirements

Issue Date: 21/05/2013

Print Date: 05/03/2015

Initial Date: Not Available

S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Propellant AS50N
Synonyms	Not Available
Proper shipping name	POWDER, SMOKELESS†
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Porous double-base smokeless powders or propellant for shotgun ammunition.
--------------------------	--

Details of the manufacturer/importer

Registered company name	Thales (Thales Australia Limited)	Thales (Thales Australia Limited)
Address	Private Bag 1 Mulwala 2647 NSW Australia	Bayly Street Mulwala 2647 NSW Australia
Telephone	Not Available	+61 3 5742 2200
Fax	Not Available	+61 3 5744 1873
Website	Not Available	Not Available
Email	Not Available	Not Available

Emergency telephone number

Association / Organisation	Not Available	Thales Australia Mulwala Facility
Emergency telephone numbers	Not Available	03 5742 2200
Other emergency telephone numbers	Not Available	Not Available

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the Model WHS Regulations and the ADG Code.




CHEMWATCH HAZARD RATINGS

	Min	Max	
Flammability	3		
Toxicity	4		
Body Contact	4		
Reactivity	4		
Chronic	2		

0 = Minimum
1 = Low
2 = Moderate
3 = High
4 = Extreme

Poisons Schedule	Not Applicable
GHS Classification [1]	Explosive Division 1.3, Acute Toxicity (Oral) Category 2, Acute Toxicity (Dermal) Category 1, Acute Toxicity (Inhalation) Category 2, STOT - RE Category 2, Chronic Aquatic Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

Label elements

GHS label elements	  
--------------------	---

SIGNAL WORD	DANGER
-------------	---------------

Hazard statement(s)

H203	Explosive; fire, blast or projection hazard
H300	Fatal if swallowed
H310	Fatal in contact with skin

Continued...

Propellant AS50N

H330	Fatal if inhaled
H373	May cause damage to organs through prolonged or repeated exposure
H412	Harmful to aquatic life with long lasting effects

Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P230	Keep wetted with phlegmatizer
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P262	Do not get in eyes, on skin, or on clothing.

Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P330	Rinse mouth.
P361+P364	Take off immediately all contaminated clothing and wash it before reuse.

Precautionary statement(s) Storage

P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P401	Store according to local regulations for explosives

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration
------	--

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
9004-70-0	>85	nitrocellulose
55-63-0	10	nitroglycerin
Not Available	<10	additives nonhazardous

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Immediately hold eyelids apart and flush the eye continuously with running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. ▶ Transport to hospital or doctor without delay. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor.
Ingestion	<ul style="list-style-type: none"> ▶ For advice, contact a Poisons Information Centre or a doctor at once. ▶ Urgent hospital treatment is likely to be needed. ▶ If swallowed do NOT induce vomiting. ▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▶ Observe the patient carefully. ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▶ Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

Symptoms of vasodilation and reflex tachycardia may present following organic nitrate overdose; most organic nitrates are extensively metabolised by hydrolysis to inorganic nitrites. Organic nitrates and nitrites are readily absorbed through the skin, lungs, mucosa and gastro-intestinal tract.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

	<p>DANGER: Deliver media remotely.</p> <ul style="list-style-type: none"> ▶ For minor fires: Flooding quantities only. ▶ For large fires: Do not attempt to extinguish.
--	---

Special hazards arising from the substrate or mixture

Fire Incompatibility	<ul style="list-style-type: none"> ▶ Avoid contact with other explosives, pyrotechnics, solvents, adhesives, paints, cleaners and unauthorized metals, plastics, packing equipment and materials. ▶ Avoid contamination with acids, alkalis, reducing agents, amines and phosphorus.
-----------------------------	--

Advice for firefighters

Fire Fighting	<p>WARNING: EXPLOSIVE MATERIALS / ARTICLES PRESENT!</p> <ul style="list-style-type: none"> ▶ Evacuate all personnel and move upwind. ▶ Prevent re-entry. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ May be explosively reactive, detonate and release much heat.
Fire/Explosion Hazard	<p>WARNING: HIGH EXPLOSION HAZARD!</p> <ul style="list-style-type: none"> ▶ Combustible. ▶ Will burn with rapidly increasing intensity of fire. ▶ Dry material is extremely sensitive to shock, friction, heat and sparks. ▶ Avoid metal to metal contact.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills	<p>Clean up all spills immediately. Avoid contact with skin and eyes. Wear impervious gloves and safety glasses. Use spark-free tools when handling Remove all ignition sources.</p>
Major Spills	<p>Clear area of personnel. Restrict access to area. Alert Fire Brigade and tell them location and nature of hazard.</p> <ul style="list-style-type: none"> ▶ May be violently or explosively reactive.
	<p>Personal Protective Equipment advice is contained in Section 8 of the MSDS.</p>

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	<p>Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this MSDS. Avoid all personal contact, including inhalation Wear protective clothing when risk of exposure occurs.</p> <ul style="list-style-type: none"> ▶ Avoid smoking, naked lights, heat or ignition sources <p>Must not be struck by metal implements.</p>
Other information	<p>Store in original containers.</p> <ul style="list-style-type: none"> ▶ No smoking, naked lights, heat or ignition sources. <p>Keep dry.</p> <ul style="list-style-type: none"> ▶ Keep storage area free of debris, waste and combustibles.

Conditions for safe storage, including any incompatibilities

Suitable container	<p>Explosives Code Packing Instruction P114(b) or 114(b) General packaging provisions of 4.1.1, 4.1.3 and special provision 4.1.5 are to be met. For UN 0160, 0161 - If outer packaging is drum then inner packaging is not required. For UN 0160, 0161 - If outer packaging is 1A2 or 1B2 metal drums then drum construction shall be that risk of explosion, by reason of increase by internal pressure from internal or external causes, is prevented. For UN 0077, 0132, 0234, 0235, 0236, packagings are to be lead free, otherwise: Inner Packagings: Bags: Paper Kraft, Plastics, Textiles - sift proof, Woven Plastic - sift proof Receptacles: Fibreboard, Metal, Paper, Plastic, Woven Plastic - sift proof Intermediate Packagings: Not necessary Outer Packagings: Boxes: Natural Wood (4C1), Natural Wood -sift proof (4C2), Plywood (4D), Reconstituted Wood (4F), Fibreboard (4G) Drums: Steel, Removable Head (1A2), Aluminium, removable head (1B2), Plywood (1D), Fibre (1G), Plastic, removable head (1H2) Check containers are clearly labelled.</p>
Storage incompatibility	<p>Segregate from strong acids strong alkalis and strong oxidisers</p> <ul style="list-style-type: none"> ▶ Avoid contact with other explosives, pyrotechnics, solvents, adhesives, paints, cleaners and unauthorized metals, plastics, packing equipment and materials. ▶ Avoid contamination with acids, alkalis, reducing agents, amines and phosphorus.



- X** — Must not be stored together
0 — May be stored together with specific preventions
+ — May be stored together

PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**Control parameters****OCCUPATIONAL EXPOSURE LIMITS (OEL)****INGREDIENT DATA**

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	nitrocellulose	Fume (thermally generated) (respirable dust)(g)	2 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	nitroglycerin	Nitroglycerin (NG)	0.46 mg/m3 / 0.05 ppm	Not Available	Not Available	Sk

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
nitrocellulose	Pyroxylin; (Cellulose tetranitrate)	15 mg/m3	170 mg/m3	990 mg/m3
nitroglycerin	Nitroglycerin	0.1 mg/m3	2 mg/m3	500 mg/m3

Ingredient	Original IDLH	Revised IDLH
nitrocellulose	Not Available	Not Available
nitroglycerin	500 mg/m3	75 mg/m3
additives nonhazardous	Not Available	Not Available

Exposure controls

Appropriate engineering controls	<p>Use in a well-ventilated area</p> <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.</p>
Personal protection	
Eye and face protection	<ul style="list-style-type: none"> ▶ Safety glasses with side shields. ▶ Chemical goggles. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Skin protection	See Hand protection below
Hands/feet protection	<p>Wear protective gloves, e.g. PVC.</p> <ul style="list-style-type: none"> ▶ Protective footwear
Body protection	See Other protection below
Other protection	<p>Overalls</p> <ul style="list-style-type: none"> ▶ Eyewash unit. ▶ Impervious apron <p>Ensure there is ready access to a safety shower</p> <ul style="list-style-type: none"> ▶ Barrier cream
Thermal hazards	Not Available

Recommended material(s)**GLOVE SELECTION INDEX**

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

Propellant AS50N Not Available

Material	CPI

* CPI - Chemwatch Performance Index

A: Best Selection

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator

Continued...

Propellant AS50N

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Small grey, green-grey or orange-grey disc shaped granules.		
Physical state	Divided Solid	Relative density (Water = 1)	Approx. 0.6
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	170
pH (as supplied)	Not Applicable	Decomposition temperature	Explosive.
Melting point / freezing point (°C)	170	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Negligible
Vapour pressure (kPa)	Negligible	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution	Not Applicable
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▶ Product is considered stable under normal handling conditions. ▶ Stable under normal storage conditions. ▶ Hazardous polymerization will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Very toxic by inhalation.
Ingestion	<p>Severely toxic effects may result from the accidental ingestion of the material; animal experiments indicate that ingestion of less than 5 gram may be fatal or may produce serious damage to the health of the individual.</p> <p>The substance and/or its metabolites may bind to haemoglobin inhibiting normal uptake of oxygen. This condition, known as "methaemoglobinemia", is a form of oxygen starvation (anoxia). Symptoms include cyanosis (a bluish discolouration skin and mucous membranes) and breathing difficulties.</p>
Skin Contact	<p>Skin contact with the material may produce severely toxic effects; systemic effects may result following absorption and these may be fatal.</p> <p>The material is not thought to be a skin irritant (as classified by EC Directives using animal models). Abrasive damage however, may result from prolonged exposures.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Bare unprotected skin should not be exposed to this material</p> <p>The material may accentuate any pre-existing dermatitis condition</p>
Eye	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may cause transient discomfort characterised by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result.

Propellant AS50N

Chronic	Substance accumulation, in the human body, is likely and may cause some concern following repeated or long-term occupational exposure. There is limited evidence that, skin contact with this product is more likely to cause a sensitisation reaction in some persons compared to the general population.	
Propellant AS50N	TOXICITY Not Available	IRRITATION Not Available
nitrocellulose	TOXICITY Oral (rat) LD50: >5000 mg/kg ^[2]	IRRITATION Not Available
nitroglycerin	TOXICITY dermal (rat) LD50: >9 mg/kg ^[1] Oral (rat) LD50: 105 mg/kg ^[2]	IRRITATION Not Available
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's msds Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

NITROCELLULOSE	No significant acute toxicological data identified in literature search.
NITROGLYCERIN	The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Substance has been investigated as a tumorigen, mutagen and reproductive effector. Equivocal tumorigen by RTECS criteria. Reproductive effector in rats.

Acute Toxicity	✔	Carcinogenicity	⊘
Skin Irritation/Corrosion	⊘	Reproductivity	⊘
Serious Eye Damage/Irritation	⊘	STOT - Single Exposure	⊘
Respiratory or Skin sensitisation	⊘	STOT - Repeated Exposure	✔
Mutagenicity	⊘	Aspiration Hazard	⊘

Legend: ✔ – Data required to make classification available
 ✘ – Data available but does not fill the criteria for classification
 ⊘ – Data Not Available to make classification

CMR STATUS

SKIN	nitroglycerin	Australia Exposure Standards - Skin	Sk
-------------	---------------	-------------------------------------	----

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
nitroglycerin	LOW (Half-life = 14 days)	LOW (Half-life = 0.73 days)

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> ▶ Recycle wherever possible. Special hazards may exist - specialist advice may be required. ▶ Consult manufacturer for recycling options. ▶ Consult State Land Waste Management Authority for disposal.
-------------------------------------	---

SECTION 14 TRANSPORT INFORMATION

Labels Required

Continued...

	
Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG)

UN number	0161
Packing group	Not Applicable
UN proper shipping name	POWDER, SMOKELESS†
Environmental hazard	No relevant data
Transport hazard class(es)	Class : 1.3C Subrisk : Not Applicable
Special precautions for user	Special provisions : Not Applicable Limited quantity : 0

Air transport (ICAO-IATA / DGR)

UN number	0161
Packing group	Not Applicable
UN proper shipping name	Powder, smokeless †
Environmental hazard	No relevant data
Transport hazard class(es)	ICAO/IATA Class : 1.3C ICAO / IATA Subrisk : Not Applicable ERG Code : 1L
Special precautions for user	Special provisions : Not Applicable Cargo Only Packing Instructions : Forbidden Cargo Only Maximum Qty / Pack : Forbidden Passenger and Cargo Packing Instructions : Forbidden Passenger and Cargo Maximum Qty / Pack : Forbidden Passenger and Cargo Limited Quantity Packing Instructions : Forbidden Passenger and Cargo Limited Maximum Qty / Pack : Forbidden

Sea transport (IMDG-Code / GGVSee)

UN number	0161
Packing group	Not Applicable
UN proper shipping name	POWDER, SMOKELESS
Environmental hazard	Not Applicable
Transport hazard class(es)	IMDG Class : 1.3C IMDG Subrisk : Not Applicable
Special precautions for user	EMS Number : F-B , S-Y Special provisions : Not Applicable Limited Quantities : 0

SECTION 15 REGULATORY INFORMATION**Safety, health and environmental regulations / legislation specific for the substance or mixture**

nitrocellulose(9004-70-0) is found on the following regulatory lists	"Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft", "Australia Hazardous Substances Information System - Consolidated Lists"
nitroglycerin(55-63-0) is found on the following regulatory lists	"Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)", "International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft", "Australia Hazardous Substances Information System - Consolidated Lists"

SECTION 16 OTHER INFORMATION**Other information**

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using

Continued...

Propellant AS50N

available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.